

2.0×1.6 SMD VCTCXO

Part Number Guide

T-V-FF.FFFM-FT-FS-OT-OP-S

T (Type 型号): TE=2.0x1.6 SMD TCXO YTE=2.0x1.6 SMD VCTCXO

V (Input Voltage 输入电压): 1, B=1.8V, 2, B=2.8V, 3, D=3.0V, etc

F (Frequency 标称频率): Normal - 5 digitals of Frequency, e.g. 13, 000M, 20, 000M

Special - All digitals of Frequency, e.g. 16, 367667M

FT (Frequency Tolerance 室温频差): A=0, 5ppm, B=1ppm, C=1, 5ppm, D=2ppm, E=2, 5ppm, etc


FS (Frequency Stability 温度频差): A=0, 5ppm, B=1ppm, C=1, 5ppm, D=2ppm, E=2, 5ppm, etc

OT (Operating Temperature 工作温度): A=0°C to +50°C, B=0°C to +70°C, C=-20°C to +70°C

D=-20°C to +75°C, E=-30°C to +75°C, F=-30°C to +85°C, G=-40°C to +85°C

OP (Output Load 输出): A=Clipped sinewave, B=Square HCMOS

S (Special Requirement 特殊要求)




Pb Free

RoHS Compliant
Directive 2002/95/EC

Mechanical Dimensions 外型尺寸

Electrical Specifications 电气参数


型号	Holder Type	2.0×1.6 SMD VCTCXO
频率范围	Frequency Range	10.000M to 52.000M
典型频率	Typical Frequency	10.000M/16.367667M/26.000M
输入电压	Supply Voltage	1.8V to 3.3V
工作温度范围	Operating Temperature Range	-10°C ~ +60°C to -40°C ~ +85°C
储存温度范围	Storage Temperature Range	-40°C to +85°C
负载	Load	(10KΩ // 10pF) ±10%
频率偏差	Frequency Tolerance	1PPM, 2.5PPM Max
频率稳定性	Frequency Stability	0.5PPM, 2.5PPM Max
频率-电压稳定性	Vs. Supply Voltage	0.2PPM
频率-负载稳定性	Vs. Load	0.2PPM
老化	Aging	1PPM
消耗电流	Current Consumption	3mA Max
电压控制范围 (VCTCXO)	Voltage control range (VCTCXO)	±9PPM ~ ±16PPM
启动时间	Start Time	3ms Max
相位噪声	offset	Phase Noise
	1Hz	-50dBc/Hz typ.
	10Hz	-80dBc/Hz typ.
	100Hz	-110dBc/Hz typ.
	1KHz	-130dBc/Hz typ.
10KHz	-145dBc/Hz typ.	



Recommended Land Pattern



Test Circuit 测试电路



Note
Please connect a bypass capacitor closely to VCC PAD.
Load capacitance (CL) includes probe and test board capacitance.

Reflow Condition 回流焊条件

